

CooCenter-S30

CooCenter-S30 is an all-in-one solution that includes a fully-featured IP PBX, Call Center, CRM and Telemarketing system. It is an ideal choice for small and micro enterprises wishing to improve internal communications, customer care, while also improving the efficiency of company telemarketing.

The CooCentre-S30 includes IP PBX features, such as voicemail, video calls, paging and intercom, IVR, call recording. Call center features including call pop-up, ACD, call queues and CRM are all available and ready to use without any license fees.

Advantages and Benefits

Cost-saving

For the price of a single CooCenter-S30 unit, customers benefit from a fully-featured IP PBX system for daily business phone calls, plus an innovative call center system solution with built-in CRM functionality for telemarketing and customer care. This combined approach significantly reduces the cost that a small business would incur if they had to procure these solutions independently.

Easy to Install and Manage

CooCenter-S30 is extremely easy to install and manage, no dedicated IT staff necessary. All features are ready to use out of the box, leading to a simple and trouble-free installation experience.

Security

A host of security related features help protect your business trade secrets. Recordings, call logs, local storage of customer data, VPN encrypted communications, PIN controlled outbound calling and different levels of system access control help ensure security of your telecommunications and business affairs.



Feature Highlights

WebRTC

By utilizing the latest WebRTC technology, from within Web extensions, agents can easily answer phone calls without handset support.

Built-in CRM

Built-in entry-level CRM system to help small businesses improve communication efficiency with customers

Call Popup

Incoming call popup on agents' Web extensions, contact's information and history of calls are all available to preview. This allows agents to be better prepared when serving customers.

IVR (Multi-layer IVRs)

Multi-layer IVRs can efficiently lead callers to IP PBX extensions and call center queue agents according to the callers requirements. High efficiency call processing improves enterprises' production and overall customer satisfaction.

Satisfaction Survey

Customer satisfaction is key to any successful business. CooCenter-S30's satisfaction survey helps enterprises establish a better customer service feedback mechanism to help ensure that customers are receiving an excellent level of service.

Specifications

Hardware	RAM	4GB DDR3L		
	Storage	16GB EMMC + 500GB HDD		
	USB (External Storage)	2xUSB (Max. 1TB mobile HDD with external power supply)		
	Ethernet	2x10/100/1000Mbps		
Telephony Interfaces	Power	AC 100~240V		
	Slot1	E1/T1/4FXO/4FXS/4GSM		
	Slot2	E1/T1/4BRI/4FXO/4FXS/4GSM		
System Capacity	Call Center Agents	60 (WebRTC or SIP extensions)		
	IP PBX Extensions	120		
	Simultaneous Calls	30		
Call Center Features	Call Popup	Call Queues	Callback Reminder	
	Remote Agents	SIP Agents	WebRTC Agents	
	ACD	Call Monitoring	Click-to-call	
	Auto Dial	Satisfaction Survey	Call Statistics	
	Built-in CRM	Questionnaire	Call Barging	
	Whisper Coaching	IVR	Voicemail	
IP PBX Features	Caller ID	Video Calls	Paging & Intercom	
	Voicemail	DID	Voicemail to Email	
	IVR	PIN Set	Call Recording	
	3-way Calling	Conference Call	Phone Provisioning	
	SIP Trunking	Blacklist	BLF	
	Feature Codes	Call Transfer	Call Parking	
	Call Forward	Call Hold	Call Waiting	
	Ring Groups	Call Pickup	MOH	
Network Features	Network Protocols	IPv4, IPv6		
	Network Mode	Static IP, DHCP, PPPoE		
	VPN (Server/Client)	L2TP, PPTP, OpenVPN, N2N		
	Transport Protocols	UDP, TCP, TLS		
	Others	DDNS, HTTPS, SSH		
Security	Firewall, IP Blacklist, Auto Defense			
Codecs & Signaling	Audio Codecs	G.711 (a, u), G.729, G.722, G.726, GSM, Speex		
	Video Codecs	H.264, H.263+, H.263, H.261		
	Signaling	SIP (RFC3261), IAX2		
	DTMF Mode	RFC2833, SIPINFO, In-band		
Environment	Operating	0°C~40°C		
	Storage	-20°C~55°C		
	Humidity	5~95% no condensation		
Dimension	Unit	440x234x44mm		
	Packing	500x315x95mm		
Packing Weight	3.8KG			

ZYCOO CO., LTD

Add: 16F, D5, Tianfu Software Park, Chengdu, China

Tel: +86(28)85337096

Email: zycoo@zycoo.com

Website: www.zycoo.com

