

CooVox-U80



CooVox U80 یک مرکز تلفنی نسل جدید و سخت افزار بسیار قدرتمند مناسب شرکت های متوسط تا بزرگ که تا ۲۰۰ داخلی و ۶۰ تماس همزمان دارند طراحی شده است. این دستگاه می تواند از ترانک های PSTN/GSM/WCDMA/ISDN/E1/T1/SIP/IAX پشتیبانی کند تا امکان ارتباطات یکپارچه VoIP را فراهم نماید. U80 یک انتخاب مقرون به صرفه، مقیاس پذیر، ایمن و قابل اعتماد است.

• مزایا:

✓ سرویس پروکسی SIP

زمانی که IP ثابت اینترنتی ندارید بنابراین باید از سرویس دهنده های DDNS یا VPN بر روی روتر خود استفاده کنید. با این سرویس نه نیاز به IP ثابت اینترنتی و نه نیاز به سرویس دهنده دیگری برای اتصال از طریق اینترنت خواهید داشت و نه نیازی به تغییر تنظیمات در زیرساخت شبکه.

✓ صورت حساب

با استفاده از سامانه صورت حساب مستقر شده دیگر نیاز به استفاده از نرم افزارهای ثالث مورد نیاز نیست. صورت حساب پیش پرداخت/پس پرداخت، اعتبار سنجی، تعیین نرخ تماس، صورت حساب های انعطاف پذیر و آمار صورت حساب و... پشتیبانی می شود.

✓ مدیریت کنفرانس تحت وب

با استفاده از این ویژگی، شروع و مدیریت یک کنفرانس از رابط وب برای شما بسیار ساده تر خواهد بود. شرکت کنندگان را دعوت کنید و آنها را کاملا در کنفرانس مدیریت کنید.

✓ راه اندازی سریع

این ویژگی امکان راه اندازی سریع و اولیه مرکز تلفن U80 را فراهم می کند. این قابلیت شامل کلیه مراحل اساسی تنظیمات در رابطه کاربری تحت وب است.

✓ آماده سازی پایانه های کلاینت

استقرار سریع و ساده کلاینت ها با استفاده از PNP و QR Code. همچنین CooCall نیز می تواند با اسکن QR Code تنظیمات را دریافت کند.

✓ داخلی تحت وب (با استفاده از WebRTC)

با استفاده از این ویژگی می توانید داخلی خود را تحت وب و بدون نیاز به هیچ گونه نرم افزار یا افزونه استفاده کنید. پیام های صوتی خود را گوش و مدیریت کنید، تماس تلفنی برقرار کنید و از تماس ورودی خود به وسیله پاپ آپ با خبر شوید.

✓ Hot Standby

با این قابلیت دو سرور U80 هم زمان اجرا می شوند. در صورت از مدار خارج شدن سرور اصلی سرور ثانویه جایگزین می شود. با استفاده از Hot Standby، دسترسی بالای خدمات تلفنی تضمین می گردد.

• مشخصات سخت افزاری:

Items	Specifications
Telephony Interfaces	8xFXO/FXS/GSM/WCDMA, 2xE1/T1, 4xBRI Interfaces
CPU	2.41GHz Dual-core Intel Processor
RAM	2GB DDR3L
Storage	16GB EMMC
USB (Extended Storage Supported)	2 (Supported File System: FAT16, FAT32, EXT3, EXT4)
Ethernet Interface	WAN, LAN (10/100/1000Mbps)
Power	AC 100-240V, Max. 1.5A
Dimension	440x222x44mm (19" 1U industry standard rack-mountable chassis)

• مشخصات نرم افزاری:

System Capacity	<ul style="list-style-type: none"> ✓ 200 Extensions ✓ 60 Simultaneous Calls ✓ 60 Conference Attendees ✓ 150hrs Recording/Voicemail (Internal Storage) ✓ 1-12 EX16S Deployment (Recommended) 	<ul style="list-style-type: none"> ✓ Unlimited IVR Levels ✓ 100 SIP/IMS Trunks (Max) ✓ 500000 CDR History ✓ 10000 Phonebook Contacts ✓ 50 Paging Members
Protocols & Codecs	<ul style="list-style-type: none"> ✓ SIP(RFC3261), IAX2 ✓ DTMF(RFC4733, SIPINFO, In-Band) ✓ Transport Protocols: UDP, TCP, TLS, SRTP ✓ Network Protocols: IPv4, IPv6, VLAN, DHCP, PPPoE, NTP, SNTP, TFTP, SSH, HTTPS, LDAP ✓ Video Codecs: VP8, H.264, H.263+, H.263, H.261 ✓ Audio Codecs: Opus, G.722, G.711(a-law, u-law), G.729, G.726, GSM, SPEEX, AMR, AMR-WB 	
Telephony Features	<ul style="list-style-type: none"> ✓ Call Queue ✓ Ring Group ✓ Call Forward ✓ Call Transfer ✓ Call Pickup ✓ Call Parking ✓ Call Waiting ✓ Speed Dial ✓ IVR (Multi-layer) ✓ Caller ID ✓ Call Spy ✓ Video Call ✓ 3-way Calling ✓ Conference Call ✓ Follow Me ✓ Call Back ✓ DISA ✓ Smart DID ✓ Blacklist ✓ Voicemail ✓ Wakeup Call ✓ PIN Code ✓ Do Not Disturb ✓ Switch Call ✓ Time Conditions ✓ Paging & Intercom ✓ One Number Stations ✓ Music On Ringback ✓ Distinctive Ringtone ✓ Auto Call Recording ✓ One Touch Recording ✓ Web Extension (WebRTC) 	
Feature Highlights	<ul style="list-style-type: none"> ✓ Quick Installation Guide ✓ Softphone APP Auto Provisioning (QR Code Scan) ✓ IP Phone Auto Provisioning (PNP, Quick Register Code) ✓ LDAP Phonebook Auto Configure (H81, H83) ✓ EX16S Auto Provisioning ✓ SIP Proxy (NAT Traversal) ✓ Voicemail to Email ✓ Fax to Email ✓ Multilingual Web UI ✓ Multilingual Voice Prompts 	
Multi-level User Administration	<ul style="list-style-type: none"> ✓ Admin user: All Privileges. ✓ Operator user: Extensions, faxes, CDR, recordings, etc. ✓ Extension user: WebRTC, recordings, voicemails, call logs, etc. ✓ Billing user ✓ Conference manager 	
Security	<ul style="list-style-type: none"> ✓ Firewall based on iptables ✓ Intrusion auto detection and prevention ✓ Geo-IP (Security policy based on IP address geographical locations) ✓ IP Black/White List ✓ Extension Permit IP 	
Network Features	<ul style="list-style-type: none"> ✓ Network (WAN): Static IP, DHCP, PPPoE ✓ VPN: PPTP, OpenVPN, IPSec, L2TP (Server and Client) ✓ Static Routing ✓ DHCP (Server and Client) ✓ DDNS (Dynamic Domain Name Server) ✓ VLAN (WAN & LAN Interface) ✓ Virtual IP ✓ Local Domain Name Service ✓ SIP Proxy (NAT Traversal) 	

ZYCOO CO., LTD

Add: 16F, D5, Tianfu Software Park, Chengdu, China

Tel: +86(28)85337096

Email: zycoo@zycoo.com

Website: www.zycoo.com

ترجمه شده توسط: مهدی ایزدی

شهریور ماه ۱۳۹۸

ZYCOO

NetTech
S U P P L I E R S
تأمین کننده تجهیزات
واحد فنی و توسعه و تحقیق